



PLATFORMS LMI

Steel feet with rubber support*

Stainless steel

Steel feet with rubber support*
*except for 60x60 and 80x80

Capacity up to 300kg

Sizes from 30x30 to 80x80 cm

Square and rectangular dimensions

grupoepelsa.com



PLATAFORMAS LMI

LMI characteristics

AISI-304 stainless steel platforms, with a robust tubular design and IP-67 protection (except with L6G_IP66 and L6F_IP65 cells), criteria that are shared for all dimensions. The stainless steel feet (except for 600x600 and 800x800) are adjustable in height with rubber support, the screws and the cover are made of AISI 304 stainless steel. The load cells are made of stainless steel (except for 600x600 and 800x800, which are made of aluminium) approved to 3000 divisions. Together with an Epelsa Group indicator, they can be supplied with EU Declaration of Conformity; with a 2.5 m cable of 6-wire hose plus aluminium shielded ground.

It is protected against static overload by a central cell stop and 4 corner stops that allow it to withstand overloads of 100% of the maximum capacity. Platforms up to 600x600 mm can work on a tabletop for standard weighing, +/- control, piece counting, manual labelling, packaging, etc., in production, material input and output, for inventories, order preparation, etc.

The 800x800 mm platforms can also work on tabletops, but due to their weight, size and capacity, they are usually installed on the floor and thus offer an economical alternative to 4-cell platforms.

Connected to the appropriate indicator, all of them can be used in combinations covered by EU Type Examination Certificate No. T11160.

Options

Generic STAINLESS STEEL column. Column height: 350mm ref.-0260557610 LMI 30x30
Generic STAINLESS STEEL column. Column height: 400mm ref.-0260557620 LMI 30x40
Generic STAINLESS STEEL column. Column height: 500mm ref.-0260557630 LMI 40x40
Generic STAINLESS STEEL column. Column height: 600mm ref.-0260557640 LMI 40x50
Generic STAINLESS STEEL column. Column height: 700mm ref.-0260557650 LMI 50x60
Y LMI 60X60
Generic STAINLESS STEEL column. Column height: 900mm ref.-0260557670 LMI 80x80

If the indicator is Orion, Cyber Plus or Dexal, you must also order the adaptation of these indicators to the column.

Option to adapt the Orion indicator to the LMI platform column Ref.-0260557710

Option to adapt the Cyber Plus indicator to the LMI platform column Ref.-0260557720

Option to adapt Dexal indicator to LMI platform column Ref.-0260557730

DIMENSIONS (without feet mm)	MIN.HEIGHT (with feet - mm)	CAPACITY KG	WEIGHT KG	LOADCELL	REFERENCE	FINISH
300 x 300 x 95	120	3*	6	B6N 7kg	0170886000	Structure and casing : AISI 304
300 x 300 x 95	120	6	6	B6N 15kg	0170887000	Structure and casing : AISI 304
300 x 300 x 95	120	15	6	B6N 30kg	0170888000	Structure and casing : AISI 304
300 x 300 x 95	120	30	6	B6N 50kg	0170889000	Structure and casing : AISI 304
300 x 400 x 95	120	30	7	B6N 50kg	0170892000	Structure and casing : AISI 304
300 x 400 x 95	120	60	7	B6N 100kg	0170893000	Structure and casing : AISI 304
400 x 400 x 95	120	15	8,5	B6N 30kg	0170895000	Structure and casing : AISI 304
400 x 400 x 95	120	30	8,5	B6N 50kg	0170896000	Structure and casing : AISI 304
400 x 400 x 95	120	60	8,5	B6N 100kg	0170897000	Structure and casing : AISI 304
400 x 400 x 95	120	150	8,5	B6N 200kg	0170898000	Structure and casing : AISI 304
400 x 500 x 95	120	30	10	B6N 50kg	0170899000	Structure and casing : AISI 304
400 x 500 x 95	120	60	10	B6N 100kg	0170900000	Structure and casing : AISI 304
400 x 500 x 95	120	150	10	B6N 200kg	0170901000	Structure and casing : AISI 304
500 x 600 x 120	145	30	20,5	BM6G 50kg	0170902000	Structure and casing : AISI 304
500 x 600 x 120	145	60	20,5	BM6G 100kg	0170903000	Structure and casing : AISI 304
500 x 600 x 120	145	150	20,5	BM6G 300kg	0170904000	Structure and casing : AISI 304
500 x 600 x 120	145	300	20,5	BM6G 500kg	0170905000	Structure and casing : AISI 304
600 x 600 x 115	155	30	18,5	L6G 50kg **	0170906000	Structure and casing : AISI 304
600 x 600 x 115	155	60	18,5	L6G 100kg **	0170907000	Structure and casing : AISI 304
600 x 600 x 115	155	150	18,5	L6G 200kg **	0170908000	Structure and casing : AISI 304
600 x 600 x 115	155	300	18,5	L6G 500kg **	0170909000	Structure and casing : AISI 304
800 x 800 x 125	160	150	32,5	L6F 250kg ***	0170910000	Structure and casing : AISI 304
800 x 800 x 125	160	300	32,5	L6F 500kg ***	0170911000	Structure and casing : AISI 304

* Approved step: 2 g (1500 divisions).

** IP65 aluminium load cell, protected with stainless steel housing and rubber cover, achieving IP66.

*** IP65 aluminium load cell

grupoepelsa.com